

Comparative statement for the Electrical items for the FY 2018-20-19

SI NO	ITEMS/SPECIFICATION	BRANDS	Units	Name of the Supplier	
				Zamin Enterprise	(P/ling)
				Rate	
	ELECTRICAL MATERIALS	All the materails should be from BSB/SQCA approved list			
A	PVC insulated Single Core Copper wire (1.1KV) garde				
1	1 sq.mm	//Royal Cable	Rolls		750
2	1.5 sq.mm	//Royal Cable	Rolls		1095
3	2 sq.mm	//Royal Cable	Rolls		NQ
4	2.5 sq.mm	//Royal Cable	Rolls		1810
5	4 sq.mm	//Royal Cable	Rolls		2590
6	6 sq.mm	//Royal Cable	Rolls		4480
7	10 sq.mm	//Royal Cable	Rolls		9450
8	16 sq.mm	// Hawell's	Rolls		20900
9	25 sq.mm	// Hawell's	Rolls		34600
10	35 sq.mm	// Hawell's	Rolls		55200
11	50 sq.mm	// Hawell's	Rolls		85300
12	70 sq.mm	// Hawell's	Rolls		115000
13	150 sq.mm	// Hawell's			NQ
B	PVC insulated single core Aluminium conductor cable 1.1KV grade				
14	35 sq.mm		Rolls		NQ
15	185 sq.mm		Rolls		NQ
16	300 sq.mm		Rolls		NQ
17	600 sq.mm		Rolls		NQ
18	800 sq.mm		Rolls		NQ
C	Power Cables (Aluminium Armoured)				
	Power Cables (1.1kV) Single Core Aluminium-Armoured, PVC insulated & sheathed				
19	150 sq.mm	// Hawell's	Meters		450

20	185 sq.mm	// Hawell's	Meters	560
21	240 sq.mm	// Hawell's	Meters	690
22	300 sq.mm	// Hawell's	Meters	790
23	400 sq.mm	// Hawell's	Meters	975
24	500 sq.mm	// Hawell's	Meters	1290
D	Power Cables (1.1kV) 2- Core Aluminium-Armoured, PVC insulated & sheathed			
25	2.5sqmm	// Hawell's	Meters	NQ
26	4 Sq.mm	// Hawell's	Meters	NQ
27	6 sq mm	// Hawell's	Meters	115
28	10 aq.mm	// Hawell's	Meters	140
29	16sq.mm	// Hawell's	Meters	149
30	25 sq.mm	// Hawell's	Meters	149
E	Power Cables (1.1kV) 3- Core Aluminium-Armoured, PVC insulated & sheathed			
31	2.5sqmm	// Hawell's	Meters	NQ
32	4 Sq.mm	// Hawell's	Meters	NQ
33	6 sq mm	// Hawell's	Meters	119
34	10 aq.mm	// Hawell's	Meters	140
35	16sq.mm	// Hawell's	Meters	155
36	25 sq.mm	// Hawell's	Meters	189
F	Power Cables (1.1kV) 3.5-Core Aluminium - Armoured, PVC insulated & sheathed			
37	25sqmm	// Hawell's	Meters	215
38	35 Sq.mm	// Hawell's	Meters	235
39	50 sq mm	// Hawell's	Meters	290
40	70 aq.mm	// Hawell's	Meters	390
41	95 sq.mm	// Hawell's	Meters	490
42	120 sq.mm	// Hawell's	Meters	615
43	150 sq.mm	// Hawell's	Meters	790
44	185 sq.mm	// Hawell's	Meters	910
45	225 sq.mm	// Hawell's	Meters	NQ
46	240sq.mm	// Hawell's	Meters	1250

	300 sq.mm		Meters	1695
47	400 sq.mm		Meters	2010
48	500 sq.mm		Meters	2650
49	630 sq.mm		Meters	3490
G	Power Cables (1.1kV) 4-Core Aluminium - Armoured, PVC insulated & sheathed			
50	2.5sqmm		Meters	NQ
51	4 Sq.mm		Meters	NQ
52	6 sq mm	// Hawell's	Meters	134
53	10 aq.mm	// Hawell's	Meters	170
54	16sq.mm	// Hawell's	Meters	199
55	25 sq mm	// Hawell's	Meters	270
56	35sqmm	// Hawell's	Meters	310
57	50sqmm	// Hawell's	Meters	390
58	70sqmm	// Hawell's	Meters	510
59	95sqmm	// Hawell's	Meters	670
60	120sq.mm	// Hawell's	Meters	770
61	225 sq.mm	// Hawell's	Meters	NQ
62	240 sq.mm	// Hawell's	Meters	1495
63	300 sq.mm	// Hawell's	Meters	1650
64	400 sq.mm	// Hawell's	Meters	2250
65	500 sq.mm	// Hawell's	Meters	3300
66	630 sq.mm	// Hawell's	Meters	3850
H	Power Cables (Aluminium Unarmoured)			
	Power Cables (1.1kV) Single Core Aluminium-Unarmoured, PVC insulated & sheathed			
67	150 sq.mm		Meters	360
68	185 sq.mm		Meters	415
69	240 sq.mm		Meters	565
70	300 sq.mm		Meters	670
71	400 sq.mm		Meters	810
72	500 sq.mm		Meters	1050

I	Power Cables (1.1kV) 2- Core Aluminium-Unarmoured, PVC insulated & sheathed			
73	2.5sqmm		Meters	NQ
74	4 Sq.mm		Meters	NQ
75	6 sq mm		Meters	74
76	10 aq.mm		Meters	95
77	16sq.mm		Meters	115
J	Power Cables (1.1kV) 3- Core Aluminium-Unarmoured, PVC insulated & sheathed			
78	2.5sqmm		Meters	NQ
79	4 Sq.mm		Meters	NQ
80	6 sq mm		Meters	95
81	10 aq.mm		Meters	118
82	16sq.mm		Meters	136
83	25 sq.mm		Meters	190
K	Power Cables (1.1kV) 3.5-Core Aluminium - Unarmoured, HD, PVC insulated & sheathed			
84	25sqmm		Meters	230
85	35 Sq.mm		Meters	275
86	50 sq mm		Meters	370
87	70 aq.mm		Meters	470
88	95 sq.mm		Meters	610
89	120 sq.mm		Meters	710
90	150 sq.mm		Meters	890
91	225 sq.mm		Meters	NQ
92	240sq.mm		Meters	1395
93	300 sq.mm		Meters	1595
94	400 sq.mm		Meters	2750
95	500 sq.mm		Meters	3200
96	630 sq.mm		Meters	4200
L	Power Cables (1.1kV) 4-Core Aluminium - Unarmoured, PVC insulated & sheathed			

96	2.5sqmm		Meters	NQ
97	4 Sq.mm		Meters	NQ
98	6 sq mm		Meters	99
99	10 aq.mm		Meters	118
100	16sq.mm		Meters	165
101	25 sq mm		Meters	240
102	35sqmm		Meters	295
103	50sqmm		Meters	370
104	70sqmm		Meters	490
105	95sqmm		Meters	580
106	120sq.mm		Meters	760
107	225 sq.mm		Meters	NQ
108	240 sq.mm		Meters	1950
109	300 sq.mm		Meters	2340
110	400 sq.mm		Meters	3120
111	500 sq.mm		Meters	3420
112	630 sq.mm		Meters	4750
L	Power Cables (Copper Conductor Armoured)			
	Power Cables (1.1kV) 2- Core Copper-Armoured, PVC insulated & sheathed			
113	2.5sqmm		Meters	300
114	4 Sq.mm		Meters	NQ
115	6 sq mm		Meters	500
116	10 aq.mm		Meters	700
117	16sq.mm		Meters	990
M	Power Cables (1.1kV) 3- Core Copper-Armoured, PVC insulated & sheathed			
118	2.5sqmm		Meters	390
119	4 Sq.mm		Meters	NQ
120	6 sq mm		Meters	590
121	10 aq.mm		Meters	890
122	16sq.mm		Meters	1300

123	25sq.mm		Meters	1950
N	Power Cables (1.1kV) 3.5-Core Copper - Armoured, PVC insulated & sheathed			
124	25sqmm		Meters	2200
125	35 Sq.mm		Meters	NQ
126	50 sq mm		Meters	NQ
O	Power Cables (1.1kV) 4-Core Copper - Armoured, PVC insulated & sheathed			
127	4 Sq.mm		Meters	600
128	6 sq mm		Meters	730
129	10 aq.mm		Meters	1050
130	16sq.mm		Meters	1525
131	25sq.mm		Meters	2480
132	35sq.mm		Meters	NQ
133	50sq.mm		Meters	NQ
P	Power Cables (Copper Conductor Unarmoured)			
	Power Cables (1.1kV) 2- Core Copper-Unarmoured, PVC insulated & sheathed			
134	2.5sqmm		Meters	99
135	4 Sq.mm		Meters	140
136	6 sq mm		Meters	195
137	10 aq.mm		Meters	395
138	16sq.mm		Meters	555
Q	Power Cables (1.1kV) 3- Core Copper-Unarmoured, PVC insulated & sheathed			
139	2.5sqmm		Meters	126
140	4 Sq.mm		Meters	195
141	6 sq mm		Meters	245
142	10 aq.mm		Meters	435
143	16sq.mm		Meters	635
144	25sq.mm		Meters	990
R	Power Cables (1.1kV) 3.5-Core Copper - Unarmoured, PVC insulated & sheathed			

145	25sq.mm		Meters	NQ
146	35sq.mm		Meters	NQ
147	50sq.mm		Meters	NQ
S	Power Cables (1.1kV) 4-Core Copper - Unarmoured, PVC insulated & sheathed			
148	4 Sq.mm		Meters	260
149	6 sq mm		Meters	380
150	10 aq.mm		Meters	595
151	16sq.mm		Meters	810
152	25sq.mm		Meters	1420
153	35sq.mm		Meters	1820
154	50sq.mm		Meters	2650
T	Flexible Cords (1.1kV) Twin-Twisted Copper - PVC insulated & sheathed			
155	0.5 sq.mm		Meters	12
U	Telephone Cable/Wire			
	Telephone wire with high density polyethene insulated, solid annealed high conductivity bare copper with 0.5mm dia, paired polyester taped and sheathed with high oxygen index fire retardant PVC compound.			
156	2 pair		Meters	50
157	5 pair		Meters	95
	Telecommunication Cable, solid annealed copper, polythene insulated, petroleum jelly filled with poly-al laminate moisture barrier 0.5mm dia unarmoured			
158	20 pair		Meters	NQ
159	50 pair		Meters	NQ
160	100 pair		Meters	NQ
	Telecommunication Cable, solid annealed copper, polythene insulated, petroleum jelly filled with poly-al laminate moisture barrier 0.5mm dia unarmoured			
161	20 pair		Meters	NQ

162	50 pair		Meters	NQ
163	100 pair		Meters	NQ
V	Thimble			
164	63A		Nos	20
165	100A		Nos	30
166	200A		Nos	35
167	250A		Nos	55
168	300A		Nos	90
W	Flat type Aluminium Alloy Thimble			
169	100A		Each	10
170	160A		Each	10
171	250A		Each	10
172	300A		Each	10
173	315A		Each	15
174	400A		Each	30
175	500A		Each	45
176	600A		Each	65
177	630A		Each	80
178	750A		Each	180
179	800A		Each	210
X	Ferrule type brass thimble			
180	6A		Each	25
181	10A		Each	30
182	16A		Each	40
183	20A		Each	55
184	25A		Each	68
185	32A		Each	90
186	40A		Each	95
187	50A		Each	130
188	63A		Each	180
189	100A		Each	210

190	125A		Each	240
191	200A		Each	265
Y	Ferrule type aluminium alloy thimble			
192	16A		Each	15
193	32A		Each	15
194	50A		Each	16
195	63A		Each	22
196	80A		Each	25
197	100A		Each	35
198	125A		Each	42
199	130A		Each	56
200	150A		Each	68
201	160A		Each	83
202	200A		Each	110
203	300A		Each	140
204	330A		Each	190
205	425A		Each	NQ
Z	HDPE Pipe pressure class 10kg/sq.cm			
206	20 mm		Meters	33
207	25 mm		Meters	40
208	32 mm		Meters	65
209	40 mm		Meters	110
210	50 mm		Meters	172
A-1	PVC Boxes			
211	PVC box 86x86x40mm		Each	75
212	PVC box 86x31x40mm		Each	75
213	PVC box 146x86x40mm		Each	140
214	1 Module	//ROMA	Each	95
215	2 Module	//ROMA	Each	120
216	3 Module	//ROMA	Each	160
217	4 Module	//ROMA	Each	210

218	5 Module	//ROMA	Each	260
219	6 Module	//ROMA	Each	390
220	7 Module	//ROMA	Each	NQ
221	8 Module	//ROMA	Each	NQ
222	9 Module	//ROMA	Each	NQ
223	10 Module	//ROMA	Each	NQ
224	11 Module	//ROMA	Each	NQ
225	12 Module	//ROMA	Each	NQ
226	13 Module	//ROMA	Each	NQ
227	14 Module	//ROMA	Each	NQ
228	15 Module	//18 Module	Each	NQ
229	PVC socket		Each	NQ
230	junction box,1 or 2 way for conduit		Each	20
231	inspection bend for conduit		Each	50
232	PVC sleev 25mm		Each	NQ
233	pvc sleev 35mm		Each	NQ
234	pvc sleev 40mm		Each	NQ
235	PVC switch box (Gang box) 1- way		Each	17
236	PVC switch box (Gang box) 2 way		Each	19
237	PVC switch box (Gang box) 3 way		Each	32
238	PVC switch box (Gang box) 4 way		Each	42
239	PVC switch box (Gang box) 5 way		Each	55
240	PVC switch box (Gang box) 6 way		Each	69
241	PVC switch box (Gang box) 7- way		Each	NQ
242	PVC switch box (Gang box) 8 way		Each	160
243	PVC switch box (Gang box) 9 way		Each	NQ
244	PVC switch box (Gang box) 10 way		Each	300
245	PVC switch box (Gang box) 11 way		Each	NQ
246	PVC switch box (Gang box) 12 way		Each	400
B-1	PVC accessories			
247	Junction box, 1 or 2 way for conduit		Each	25

248	Inspection bend for conduit		Each	50
249	PVC Socket		Each	18
C-1	Wooden boxes	//PVC Box		
250	Box 75x75x38mm		Each	NQ
251	Box 100x100x38mm		Each	NQ
252	Box 150x150x38mm		Each	NQ
253	Box 180x150x38mm		Each	NQ
254	Box 100x75x38mm		Each	NQ
255	Box 200x100x38mm		Each	NQ
256	Box 250x200x38mm		Each	NQ
257	Box 300x200x38mm		Each	NQ
258	Box 450x300x38mm		Each	NQ
D-1	Metal boxes			
259	1 Module	//ROMA	Each	180
260	2 Module	//ROMA	Each	180
261	3 Module	//ROMA	Each	260
262	4 Module	//ROMA	Each	290
263	5 Module	//ROMA	Each	NQ
264	6 Module	//ROMA	Each	360
265	7 Module	//ROMA	Each	NQ
267	8 Module	//ROMA	Each	390
268	9 Module	//ROMA	Each	NQ
269	10 Module	//ROMA	Each	NQ
E-1	Metal boxes	//M.S. Boy		
270	Metal, 75x75x60 mm		Each	95
271	Metal, 60x60x60 mm		Each	125
272	Metal, 86x86x40 mm		Each	200
273	Metal, 100x100x60 mm		Each	260
274	Metal, 86x31x40 mm		Each	NQ
275	Metal, 146x86x40		Each	NQ
276	Metal, 150x100x60 mm		Each	NQ

277	Metal, 150x150x60 mm		Each	NQ
278	Metal, 180x100x60 mm		Each	NQ
279	Metal, 180x150x60 mm		Each	NQ
280	Metal, 200x125x60 mm		Each	NQ
281	Metal, 200x150x60 mm		Each	265
282	Metal, 250x200x60 mm		Each	340
283	Metal, 300x200x60 mm		Each	450
284	Metal, 200x150x100 mm		Each	NQ
285	Metal, 200x250x100 mm		Each	NQ
286	Metal, 200x300x100 mm		Each	NQ
287	Metal, 250x300x100 mm		Each	NQ
288	Metal, 300x380x100 mm		Each	NQ
289	Metal, 300x450x100 mm		Each	NQ
290	Laminated Sheet Cover for metal boxes		Each	NQ
F-1	PVC Casing & Cappings (Double Locking)			
291	12x12 mm		Piece	NQ
292	12x10 mm		Piece	NQ
293	15x10 mm		Piece	45
294	20x10 mm		Piece	55
295	20x12 mm		Piece	60
296	25x10 mm		Piece	65
297	30x10 mm		Piece	95
298	40x20 mm		Piece	105
299	50x20 mm		Piece	NQ
300	Corner/Tee		Piece	6
G-1	Busbars & busbar chambers,copper busbar &MS busbar chamber			
301	2 strips,300mm,bars 100A	//Geco	Each	NQ
302	4 strips,300mm bar,100A	//Geco	Each	3750
303	4 strips,300mm bar,200A	//Geco	Each	4900
304	2 strips,450mm bar,100A		Each	NQ
305	4 strips,450mm bar,100A		Each	5300

306	4 strips,450mm bar,200A		Each	6700
307	4 strips,600mm bar,100A or 6 strips	//6 strips	Each	5300
308	4 strips,600mm bar,200A or 6 strips	//6 strips	Each	6700
309	4 strips,600mm bar,300A or 6 strips	//6 strips	Each	11300
H-1	Aluminium alloy/ aluminium busbar complete			
310	4 strips, 600mm bar 300A		Each	NQ
311	4 strips, 600mm bar, 400A		Each	NQ
312	4 strips, 600mm bar, 400A		Each	NQ
313	4 strips, 900mm bar,400A		Each	NQ
314	4 strips, 900mm bar, 800A		Each	NQ
315	4 strips, 1350mm bar, 400A		Each	NQ
316	4 strips, 1350mm bar, 600A		Each	NQ
317	4 strips, 1350mm bar, 800A		Each	NQ
I-1	Control-Gear & Switch Boards			
	Wall mounting Fuse Switch Units sheet steel enclosure			
318	TPN, 20A, 415V		Each	NQ
319	TPN, 32A,415V, SFU	// Hawell's	Each	2100
320	TPN, 63A,415V, SFU	// Hawell's	Each	3900
321	TPN, 200A,415V, FSU	// Hawell's	Each	10200
322	TPN, 250A, 415V, FSU	// Hawell's	Each	NQ
323	TPN, 315A, 415V, FSU		Each	15900
324	TPN, 125A, 415V, SFU		Each	10200
325	TPN, 400A,415V, FSU		Each	25900
326	TPN, 500A,415V, FSU		Each	NQ
327	TPN, 630A,415V, FSU		Each	NQ
328	TPN, 750A,415V FSU		Each	NQ
329	TPN, 800A,415V, FSU		Each	NQ
330	4 pole, 500A, 415V, FSU		Each	NQ
331	4 pole, 750A, 415V, FSU		Each	NQ
J-1	Panel mounting disconnecter FSU complete with front drive mechanism with door interlock			

	(HRC fuse)			
332	4 pole, 250A, 415V, FSU		Each	19000
333	4 pole, 400A, 415V, FSU		Each	38000
334	4 pole, 125A, 415V, SFU		Each	NQ
335	3 pole, 32A, 415V, SFU		Each	NQ
336	3 pole, 63A, 415V, SFU		Each	8200
337	3 pole, 125A, 415V, SFU		Each	NQ
338	3 pole, 250A, 415V, FSU		Each	NQ
339	3 pole, 400A, 415V, FSU		Each	29000
K-1	HRC Fuses			
340	20A, 415V size 0		Each	70
341	32A, 415V size 0		Each	70
342	63A, 415V size 0		Each	90
343	125A, 415V size 1		Each	210
344	200A, 415V size 1		Each	310
345	250A, 415V size 1		Each	370
346	315A, 415V size 2		Each	550
347	400A, 415V size 2		Each	915
348	500A, 415V size 3		Each	990
349	630A, 415V size 3		Each	1690
350	750A, 415V size 3		Each	NQ
351	800A, 415V size 3		Each	1890
L-1	Earth Leakage			
	Earth leakage module, 4 pole, 415 volt A.C			
352	125A		Each	NQ
353	160A		Each	NQ
354	250A		Each	NQ
355	400A		Each	NQ
356	630A		Each	NQ
M-1	Miniature Circuit Breaker (MCB)			
	SP MCB 230 volt A.C			

357	6A	// Hawell's	Each	168
358	10A	// Hawell's	Each	168
359	16A	// Hawell's	Each	168
360	20A	// Hawell's	Each	168
361	25A	// Hawell's	Each	168
362	32A	// Hawell's	Each	168
363	40A	// Hawell's	Each	550
364	63A	// Hawell's	Each	710
N-1	2 pole MCB, 230 volt A.C			
365	6A	// Hawell's	Each	650
366	10A	// Hawell's	Each	650
367	16A	// Hawell's	Each	650
368	20A	// Hawell's	Each	650
369	25A	// Hawell's	Each	650
370	32A	// Hawell's	Each	650
371	40A	// Hawell's	Each	1250
372	50A	// Hawell's	Each	NQ
373	63A	// Hawell's	Each	1490
O-1	TPN MCB,415V,A.C			
374	6A	// Hawell's	Each	1600
375	10A	// Hawell's	Each	1600
376	16A	// Hawell's	Each	1600
378	20A	// Hawell's	Each	1600
379	25A	// Hawell's	Each	1600
380	32A	// Hawell's	Each	1600
381	40A	// Hawell's	Each	2010
382	50A	// Hawell's	Each	NQ
383	63A	// Hawell's	Each	2250
P-1	DP isolator,230V			
384	32A		Each	NQ
385	40A	// Hawell's	Each	540

386	63A	// Hawell's	Each	650
Q-1	Residual Current Circuit Breaker(RCCB), 2-Pole			
387	16A	// Hawell's	Each	2600
388	25A	// Hawell's	Each	2600
389	32A	// Hawell's	Each	2750
390	40A	// Hawell's	Each	2750
391	63A	// Hawell's	Each	3700
R-1	4 pole RCCB , 415 voltA .C,30mA			
392	16A	// Hawell's	Each	NQ
393	25A		Each	3700
394	32A		Each	NQ
395	40A	// Hawell's	Each	4200
396	63A	// Hawell's	Each	4800
S-1	MCCBs - 3 POLE - 1 1KVA (25KA)			
397	63A	// Hawell's	Each	4100
398	100A	// Hawell's	Each	4600
399	125A	// Hawell's	Each	7200
400	200A	// Hawell's	Each	11600
401	250A	// Hawell's	Each	16100
T-1	MCCBs - 3 POLE - 1 1KVA (16KA)			
402	63A	// Hawell's	Each	4100
403	100A	// Hawell's	Each	4600
404	125A	// Hawell's	Each	5100
U-1	MCCBs - 3 POLE - 1 1KVA (36KA)	//35KA		
405	125A	// Hawell's	Each	7500
406	160A	// Hawell's	Each	9900
407	250A	// Hawell's	Each	16400
V-1	MCCBs - 4 POLE - 1 1KVA (16KA)			
408	63A	// Hawell's	Each	4600
409	100A	// Hawell's	Each	5100
410	125A	// Hawell's	Each	5600

W-1	MCCBs - 4 POLE - 1 1KVA (25KA)			
411	63A	// Hawell's	Each	6100
412	100A	// Hawell's	Each	6700
413	125A	// Hawell's	Each	7700
X-1	MCCBs - 4 POLE - 1 1KVA (36KA)	//35 KA		
414	125A	// Hawell's	Each	9900
415	160A	// Hawell's	Each	18900
416	250A	// Hawell's	Each	25200
Y-1	MCCBs - 4 POLE - 1 1KVA (70KA)			
417	250A	// Hawell's	Each	NQ
418	400A	// Hawell's	Each	NQ
419	630A	// Hawell's	Each	NQ
420	800A	// Hawell's	Each	NQ
Z-1	Isolators TPN - 415Volts	//FP		
421	40A	// Hawell's	Each	1150
422	63A	// Hawell's	Each	1490
423	100A	// Hawell's	Each	1700
424	200A	// Hawell's	Each	NQ
425	250A	// Hawell's	Each	NQ
A-2	Distruption Board (DB)			
	SPN DB,230 volt A .C, without door/single door			
426	4 way	// Hawell's	Each	710
427	6 way	// Hawell's	Each	870
428	8 way	// Hawell's	Each	890
429	12 way	// Hawell's	Each	1150
430	16 way	// Hawell's		1450
B-2	TPN DB,230 volt AC, without door/single door			
431	4 way	// Hawell's	Each	1900
432	6 way	// Hawell's	Each	2150
433	8 way	// Hawell's	Each	2800
434	12 way	// Hawell's	Each	3600

435	16 way	// Hawell's	Each	NQ
C-2	DBs Single door type (For Single Phase)			
436	4way	//Geco	Each	540
437	6way	//Geco	Each	680
438	8way	//Geco	Each	790
439	12way	//Geco	Each	960
440	2 way	//Geco	Each	NQ
D-2	DBs Double door type (for single phase)			
441	4way	// Hawell's	Each	2100
442	6way	// Hawell's	Each	2400
443	8way	// Hawell's	Each	2900
444	12way	// Hawell's	Each	4100
E-2	DBs TPN (Triple pole with nutral) Single door			
445	4 way	// Hawell's	Each	NQ
446	6 Way	// Hawell's	Each	NQ
447	8 Way	// Hawell's	Each	NQ
448	12 way	// Hawell's	Each	NQ
F-2	DBs TPN (Triple pole with nutral) Double door			
449	4 Way	// Hawell's	Each	NQ
450	6 way	// Hawell's	Each	NQ
451	8 way	// Hawell's	Each	NQ
452	12 Way	// Hawell's	Each	NQ
G-2	Lightning Finial			
	Copper tube finial with base plate 85x3mm			
453	25mm dia, 300mm long with single prong		Nos	NQ
454	25mm dia, 900mm long with four prong		Nos	NQ
H-2	G.I tube finial with copper base plate 85x6mm			
455	25mm dia, 300mm long with single prong		Nos	NQ
I-2	Panel Mounting MCCB			
456	3 pole, 16KA, MCCB 63A, 415V	// Hawell's	Each	4000
457	3 pole, 16KA, MCCB 100A, 415V	// Hawell's	Each	4100

458	3 pole, 16KA, MCCB 125A, 415V	// Hawell's	Each	4100
459	4 pole, 16KA, MCCB 63A, 415V	// Hawell's	Each	4600
460	4 pole, 16KA, MCCB 100A, 415V	// Hawell's	Each	5200
461	4 pole, 16KA, MCCB 125A, 415V	// Hawell's	Each	5700
462	3 pole, 25KA, MCCB 63A, 415V	// Hawell's	Each	4100
463	3 pole, 25KA, MCCB 100A, 415V	// Hawell's	Each	4500
464	3 pole, 25KA, MCCB 125A, 415V	// Hawell's	Each	4700
465	4 pole, 25KA, MCCB 63A, 415V	// Hawell's	Each	5900
466	4 pole, 25KA, MCCB 100A, 415V	// Hawell's	Each	6100
467	4 pole, 25KA, MCCB 125A, 415V	// Hawell's	Each	7500
468	3 pole, 36KA, MCCB 125A, 415V	// Hawell's 35 KA	Each	7900
469	3 pole, 36KA, MCCB 160A, 415V	// Hawell's 35 KA	Each	9500
470	3 pole, 36KA, MCCB 250A, 415V	// Hawell's 35 KA	Each	14100
471	4 pole, 36KA, MCCB 125A, 415V	// Hawell's 35 KA	Each	14100
472	4 pole, 36KA, MCCB 160A, 415V	// Hawell's 35 KA	Each	19000
473	4 pole, 36KA, MCCB 250A, 415V	// Hawell's 35 KA	Each	25100
474	4 pole, 70KA, MCCB 250A, 415V		Each	NQ
485	4 pole, 70KA, MCCB 400A, 415V		Each	NQ
476	4 pole, 70KA, MCCB 630A, 415V		Each	NQ
478	4 pole, 70KA, MCCB 800A, 415V		Each	NQ
J-2	Luminaires (Surface / ceiling mounted, GLS lamp)			
479	Globe dia 150mm, 1x60W	// Hawell's	Each	NQ
380	Globe dia 200mm, 1x60W	// Hawell's	Each	NQ
481	Globe dia 250mm, 1x60W	// Hawell's	Each	NQ
482	Square louvered, 1x60W	// Hawell's	Each	NQ
483	Special drumlite, dia 175mm milky, 1x60W		Each	NQ
484	Special drumlite dia 225mm milky, 1x60W		Each	NQ
485	Spot light 235mm, reflector dia 130mm, 1x60W		Each	NQ
486	Spot light 245mm, reflector dia 100mm, 1x60W		Each	NQ
487	Clamp light 225mm, dia 110mm, 1x60W		Each	NQ
488	Clamp light 160mm, 100W		Each	NQ

489	Rail light 225mm, 2x60W (R)		Each	NQ
490	Rail light 160mm, 2x100W (R)		Each	NQ
491	Rail light 225mm, 3x60W (R)		Each	NQ
492	Rail light 160mm, 3x100W (R)		Each	NQ
493	Wall bracket 225mm, 1x60W		Each	1900
494	Wall bracket 230mm, 1x60W		Each	2400
495	Wall bracket 160mm, 1x60W		Each	2400
496	Wall bracket 185mm, 1x60W		Each	2400
497	Double wall bracket 200mm, 2x60W		Each	2700
498	Double wall bracket 160mm, 2x60W		Each	NQ
499	Single swivel wall bracket 375mm, 1x60W		Each	NQ
500	Double mirror light 610mm, 2x60W		Each	3600
501	Double mirror light 460mm, 2x60W		Each	3400
502	Single picture light 200mm, 1x60W		Each	3400
503	Pendant down lighter 215mm, 1x60W		Each	NQ
504	Pendant lantern type 460mm, 1x60W		Each	NQ
505	Pendant 460mm, 3x60W		Each	NQ
506	Recessed down lighter square 170-190mm, 1x100W		Each	4900
507	Recessed down lighter, round 180mm, 1x100W		Each	2900
508	Recessed down lighter, round 165mm, 1x60W (R)		Each	2900
509	Semi recessed down lighter square 170-200mm, 1x100W		Each	NQ
510	Semi recessed down lighter, round 90-95mm, 1x100W		Each	NQ
511	Semi recessed down lighter, side entry 205mm, 1x60W (R)		Each	NQ
512	Wall bracket louvered 275mm, 1x60/100W		Each	NQ
513	Bulk head die cast aluminium body, weather proof gasket, wire guard, 1x60/100W		Each	9900
514	Post top dia 325-380mm, 1x60/100W		Each	NQ
K-2	Switches & Sockets			
515	6A switch SP 1-way	//Anchor ROMA	Each	75
516	6A switch SP 1-way with indicator (Modular Type)	//ROMA	Each	120

517	6A switch SP 2-way	//Anchor	Each	95
518	6A switch SP 2-way with indicator (Modular Type)		Each	180
519	16A swicth SP 1-way	//Anchor ROMA	Each	180
520	16A swicth SP 1-way with indicator	//ROMA	Each	210
521	16A swicth SP 2-way	//Anchor	Each	180
522	16A fuse unit	//Anchor	Each	140
523	2-pin 6A socket outlet	//Anchor	Each	35
524	3-pin, 6A socket outlet, shuttered	//ROMA	Each	60
525	3-pin, 16A socket outlet, shuttered	//ROMA	Each	70
526	3 pin, 6A switch/socket combined, shuttered	//ROMA	Each	NQ
527	5 pin, 6A switch/socket combined, shuttered	//Anchor Renta	Each	NQ
528	3 pin, 16A switch/socket combined, shuttered	//Anchor Renta	Each	140
529	5/6 pin, 6/16A socket outlet, shuttered	//Anchor Renta	Each	140
530	3 pin, 16A switch/socket combined, shuttered (Modular Type)	//Anchor ROMA	Each	725
531	5/6 pin, 6/16A switch/socket combined, shuttered (Modular Type)	//Anchor ROMA	Each	840
532	5-pin universal socket outlet	//Anchor ROMA	Each	90
533	3-pin top,16A	//Anchor ROMA	Each	90
534	Multi plug,16A	//Anchor ROMA	Each	140
535	3- pin top,5A	//Anchor ROMA	Each	110
536	Dimmer / regulator small	//Anchor ROMA	Each	295
537	Dimmer / regulator big	//Anchor ROMA	Each	395
538	TV coaxial socket	//Anchor ROMA	Each	260
539	RJ 45 computer socket	//Anchor ROMA	Each	460
540	RJ 11 telephone socket	//Anchor ROMA	Each	410
541	Bell push 6A	//Anchor ROMA	Each	140
542	Plate 1-module with frame	//ROMA	Each	98
543	Plate 2-module with frame	//ROMA	Each	98
544	Plate 3-module with frame	//ROMA	Each	130
545	Plate 4-module with frame	//ROMA	Each	155
546	Plate 6-module with frame	//ROMA	Each	220

547	Plate 8-module with frame	//ROMA	Each	265
548	Plate 9-module with frame	//ROMA	Each	NQ
549	Plate 10-module with frame	//ROMA	Each	NQ
L-2	 Holders & Plugs			
550	Batten holder (heavy duty, brass)	//Anchor Plastic	Each	65
551	Plain pendant holder (bakelite)	//Anchor Plastic	Each	27
552	Angle holder (heavy duty)	//Anchor Plastic	Each	30
553	Cord-grip, PVC 2-core	//Anchor Plastic	Each	NQ
554	Twin flexible wire (twisted) heavy duty		Each	900
555	Ceiling Rose, 2 plate (PVC) 6A		Each	30
M-2	 Indoor Luminaires			
	Prewired Indoor fluorescent lamp luminaires (CRCA sheet housing, steel) for wall/ceiling			
556	Strip Rail, 18/20 W, LPF	//CGL Frame	Each	NQ
557	Decorative, box type 18/20 W, LPF		Each	1900
558	Mounting channel, 18/20 W, LPF		Each	NQ
559	Strip Rail, 36/40 W, LPF		Each	3900
560	Decorative, box type 36/40 W, LPF	//(1x36)TCS605	Each	2500
561	Mounting channel, 36/40 W, LPF		Each	3500
562	Mounting box, 1x36/40 W, HPF		Each	3500
563	Mounting box, 2x36/40 W, HPF	//TCS-605	Each	3900
564	Industrial box, 1x36/40 W, HPF	//TCS-606	Each	3900
N-2	 Indoor fluorescent lamp luminaires, steel rail, Industrial box			
565	Vitreous enamel reflector, 1x36/40 W, HPF		Each	NQ
566	Stove enamel reflector, 2x36/40 W, HPF		Each	NQ
567	Stove enamel reflector 1x36/40 W, HPF		Each	NQ
568	Vitreous enamel reflector, 2x36/40 W, HPF		Each	NQ
O-2	 Indoor decorative fluorescent lamp luminaires, steel rail, surface mounting box			
569	Polysterene structured louvere and reflector, 2x36/40 W, HPF		Each	6100
570	Metal louvere and reflector, 2x36/40 W, HPF		Each	6100

571	Opal acrylic diffuser and reflector, 2x36/40 W, HPF		Each	NQ
572	Opal acrylic diffuser & reflector, 1x36/40 W, HPF		Each	NQ
573	PrisMTic louvere and reflector, 2x36/40 W, HPF		Each	5900
574	Opal acrylic diffuser, 2x36/40 W, HPF		Each	NQ
575	Opal acrylic diffuser and reflector, 2x18/20 W, HPF		Each	6200
P-2	Indoor decorative fluorescent lamp luminaires, steel rail, recessed, Mounting box			
576	PrisMTic louvere and reflector, 2x36/40 W, HPF		Each	9000
577	Opal acrylic diffuser, 2x36/40 W, HPF		Each	9000
578	Structured louvere and reflector, 2x36/40 W, HPF		Each	11500
Q-2	Indoor decorative fluorescent lamp luminaires, steel rail, surface/recessed, Mounting box			
579	PrisMTic louvere and reflector, 4x18/20 W, HPF		Each	12000
580	Opal acrylic diffuser, 4x18/20 W, HPF		Each	12000
581	Structured louvere and reflector, 4x18/20 W, HPF		Each	14000
582	Mirror optic louvere and reflector, 2x18/20 W, HPF		Each	14000
583	Mirror optic louvere, 2x36/40 W, HPF		Each	14000
584	Wide spread mirror optic and reflector, 2x36/40 W, HPF		Each	13000
585	Compact fluorescent lamp (CFL) Estone supper 20 W		Each	310
586	Supplying of prewired indoor rails and wall brackets on surface/ceiling mounted luminaires suitable for GLS lamp for maximum wattage upto 1x60W complete with all accessories such as base, holder, reflector, rails, glass globe etc. but without bulb.		Each	1900
587	Special drumlite dia 225, milky, projection 115mm, finish-painted		Each	NQ
588	Wall bracket Globe light 250mm diameter, height 295mm finish painted, glass frosted, white colour (0929 01)		Each	NQ
589	3 Light Maryland pendent, glass: Frosted, GLS- 3X60W (2655 01) white colour		Each	NQ
590	Decorative CFL Striplite for wall/Celing mounting, 1xPL-L-36W		Each	NQ

591	New brick light Non-Louvered PL-C, PL-2x13W, White colour (540P 01) size 230/100mm		Each	NQ
592	Square Surface Mounted (600mmx600mm) Acrylic Clean Room Square FTL- 4x18W, -- White powder coated CRCA sheet steel housing Clear, Milky 2mm-3mm Acrylic diffuser fitted in a louver frame complete with slim open type low loss copper		Each	15000
593	Out door lighting Metal Halide Flood (S) C, MHDE-150W, white colour (ODFLMH150), Glass: Clear Toughen, Material: Die Cast Aluminium, Size 300/185mm		Each	NQ
594	wing (accessories) Tabular Suspension, white colour		Each	NQ
595	Non integral asymmetric floodlight luminaries with die cast aluminium housing with external CG Box (IP 65)_RVP 501/1xSON-T 1000W, (including separate CG Box) 1xSON-T 1000W.		Each	41000
596	Recessed down lights, round with glass PL-C-22 (PL-1X18W), glass center frosted, white , 02NDN 01		Each	3100
597	Bulk Head Fitting 60 watt		Each	1050
598	Recessed down lights, round with glass PL-C-18 (PL-2X18W), glass center frosted, white , 02NBR 01		Each	3900
R-2	Outdoor Luminaries			
	Street Lighting			
599	1x36/40 W, HPF		Each	2000
600	2x36/40 W, HPF		Each	4000
601	1x18/20 W, HPF		Each	NQ
602	1x70 W, (E) SON(BC)		Each	5600
603	1x70 W, (I)SON(BC)		Each	5600
604	1x100 W, SON(BC)		Each	NQ
605	1x250 W, SON(ES)		Each	8000
606	1x80 W, HPL-N(BC)		Each	NQ
607	1x125 W, HPL-N(BC)		Each	4200
608	1x250 W, HPL-N(ES)		Each	7600
609	1xSON 70W (E) HPF		Each	4800

610	1x125 watt HPL-N(ES)		Each	4700
611	1x250 watt HPL-N(ES)		Each	7900
612	1x125 watt HPL-N(BC)		Each	3900
613	1x70 watt (E) SON (BC)		Each	4100
614	1x100 watt SON (BC)		Each	NQ
615	1x250 watt SON (BC)		Each	NQ
616	HPL -N lamp80 watt (BC/ES)		Each	NQ
617	HPL -N lamp 125 watt (BC/ES)		Each	510
618	HPL -N lamp 250 watt (BC/ES)		Each	715
619	HPL- SON-T lamp 150 watt(ES)		Each	790
620	HPL - SON-T lamp 250 watt(ES)		Each	950
S-2	Post Top Lantern			
621	1x80 W, HPL-N(BC)		Each	NQ
622	1x125 W, HPL-N(ES)		Each	4900
623	1x160 W, ML(ES)		Each	NQ
624	1x70 (E) W, SON(BC)		Each	5800
625	1x70(l) W, SON(BC)		Each	5900
T-2	Under water lighting			
626	60/75/100 W (R), (BC) for depth<0.60m		Each	NQ
U-2	Flood Light Luminiare			
627	2x250/400 W, HPL-N(ES)		Each	34000
628	2x250/400 W, SON-T(ES)		Each	31000
629	1x500 W, (ES)		Each	NQ
630	1x250/400 W, HPI-T		Each	13900
631	Halogen lamp, 1x500 W		Each	1100
632	Halogen lamp, 1 or 2x1000 W		Each	1700
V-2	Industrial well glass			
634	GLS 1x200/300 W (ES)		Each	NQ
635	1x80/125 W HPL-N(BC)		Each	NQ
636	1x70/100 W (E) SON(BC)		Each	NQ
W-2	Flame proof Industrial well glass			

637	1x60/200 W (BC/ES)		Each	NQ
638	1x80/125 W HPL-N(BC)		Each	NQ
639	1x160 W ML-N(ES)		Each	NQ
X-2	Flame proof bulk head			
640	1x60/200 W GLS(BC/ES)		Each	NQ
641	1x80/125 W (BC)		Each	NQ
642	1x160 W ML-N(ES)		Each	NQ
Y-2	Call bell 250 volt A.C			
643	Gong bell assembly		Each	240
645	Buzzer bell assembly		Each	140
646	Musical bell assembly		Each	290
Z-2	Lighting track 250 volt A.C, for 60 W reflector lamp for museum or decorated shop			
647	0.5m		Nos	NQ
648	1.0m		Nos	NQ
649	2.0m		Nos	NQ
A-3	L a m p s			
	GLS lamp 250 volt A.C			
650	40 W (BC)		Each	25
651	60 W (BC)		Each	30
652	100 W (BC)		Each	35
653	150 W (ES)		Each	NQ
654	200 W (ES)		Each	NQ
655	300 W (ES)		Each	NQ
656	500 W (ES)		Each	NQ
657	Metal halide lamp (MHDE- 150 W)		Each	NQ
658	CFL (2x13W)		Each	NQ
659	Halogen lamps (HAL-220V/150W)		Each	NQ
660	FTL- 4x18 W (for acrylic Clean Room square Type-C)		Each	NQ
661	1xPL-L 36W lamp		Each	NQ
662	PL-C-22 (PL-1x18W)		Each	5400

663	PL-C-18 (PL-2x18W)		Each	2300
664	CFL Compact Bulb (20 Watt)		Each	210
665	CFL Compact Bulb (75Watt)	//85 Watt	Each	NQ
666	CFL Compact Bulb (100 Watt)		Each	NQ
667	Mirror Light		Each	4300
B-3	Reflector lamp 250 volt A.C			
668	60 W (R) 63(BC)		Each	NQ
669	75 W (R) 95(BC/ES)		Each	NQ
670	100 W (R) 95(BC/ES)		Each	NQ
671	150 W (R) 95(BC/ES)		Each	NQ
C-3	High pressure mercury vapour lamp 250 volt A.C			
672	HPL-N 80 W (BC/ES)		Each	750
673	HPL-N 125 W (BC/ES)		Each	700
674	HPL-N 250 W (ES)		Each	1100
675	HPL-N 400 W (ES)		Each	NQ
D-3	High pressure sodium vapour lamp 250 volt A.C			
676	SON-T 70 W (E)(BC)		Each	510
677	SON-T 70 W (I) (BC)		Each	510
678	SON-T 150 W (ES)		Each	640
679	SON-T 250 W (ES)		Each	790
680	SON-T 400 W (ES)		Each	1400
681	Osram Vialox Nav-T (Son-T 1000W) (E) HPS High Pressure Sodium Lamp		Each	NQ
E-3	Metal halide lamp 250 volt A.C			
682	HPI-T 250 W (ES)		Each	1100
683	HPI-T 400 W (ES)		Each	1450
F-3	Halogen lamp 250 volt A.C			
684	7785 R 500 W		Each	NQ
685	12013 R 1000 W		Each	NQ
F-3	Argenta superlux lamp 250 volt A.C			
686	60 W (BC)		Each	NQ
G-3	Special incandescent lamp 250 volt A.C			

687	15 W (BC) pigmy		Each	NQ
H-3	Fluorescent lamp 250 volt A.C			
688	TL 18/20 W		Each	55
689	TL 36/40 W		Each	55
690	TLF 36/40 W		Each	55
I-3	Lamp Shades			
691	150mm dia		Each	400
692	180mm dia		Each	600
J-3	Glass lengum shade			
693	150mm dia		Each	NQ
694	180mm dia		Each	NQ
K-3	Heat resistant proof plastic conical shade			
695	150mm dia		Each	NQ
696	Heat resistant proof plastic coolican shade		Each	NQ
697	150mm dia		Each	NQ
L-3	F a n s			
698	1400 rpm, 900mm sweep		Each	1850
699	1400 rpm, 1200mm sweep		Each	1950
700	1400 rpm, 1400mm sweep		Each	2900
M-3	Exhaust fan 240 volt A.C			
701	900 rpm, 300mm sweep		Each	2000
702	900 rpm, 380mm sweep		Each	2850
703	900 rpm, 450mm sweep		Each	8500
704	1400 rpm, 300mm sweep		Each	2400
705	1400 rpm, 380mm sweep		Each	4200
706	1400 rpm, 450mm sweep		Each	11200
N-3	Aluminium louvere with frame			
707	300mm sweep		Each	NQ
708	380mm sweep		Each	NQ
709	450mm sweep		Each	NQ
O-3	Street/Compound Light Pole			

	Steel Tubular Pole with base plate			
710	5.5m, 4.5mm thick		Each	NQ
911	5.5m, 4.8mm thick		Each	NQ
712	5.5m, 5.4mm thick		Each	NQ
P-3	Swaged Street Light Steel Tubular Pole (410 MPa) with base plate			
713	8.5m, 158 kg		Each	NQ
714	8.5m, 148 kg		Each	NQ
715	8.5m, 141 kg		Each	NQ
716	8.5m, 151kg		Each	NQ
P-3	P o l e C a p			
717	Pole cap wih arm bracket 1.1m and outer dia 50/60mm			
718	Single arm		Each	NQ
719	Double arm		Each	NQ
720	Triple arm		Each	NQ
721	MS junction box out door duty, fabricated with 14SWG MS sheet		Each	NQ
Q-3	<i>EARTHING</i>			
722	GI Earth Plate 600x600x6mm		Each	1610
723	GI Earth Plate 300x300x6mm		Each	800
724	Copper earth plate 600x600x3mm		Each	6900
725	Copper earth plate 300x300x3mm		Each	4500
726	8SWG GI Wire		Meter	13
727	6 SWG GI wire		Meter	NQ
728	14SWG GI wire		Meter	10
729	Metal strip 0.5m		Meter	200
R-3	<i>Trimer Switch</i>			
730	Digital 24hrs/24hrs		Nos	10500
731	Digital 7days/24hrs		Nos	16200
S-3	<i>M.S Conduit</i>			
732	15mmx 1.6mm		Meters	80
733	20mmx 1.6mm		Meters	100

734	25mmx1.6mm		Meters	140
735	32mmx2mm		Meters	210
736	40mmx2mm		Meters	275
737	50mmx 2mm		Each	410
738	junction box,1 or 2 way		Each	30
739	inspection bend		Each	75
740	socket for conduit		Each	20
741	M.S saddle for different size		Each	8
T-3	PVC conduit			
742	20mm		Meter	40
743	25mm		Meter	45
744	32mm		Meter	NQ
745	40mm		Meter	NQ
746	50mm		Each	NQ
747	PVC boxes		Each	12
748	PVC box 86x86x40mm		Each	40
749	PVC box 86x31x40mm		Each	40
750	PVC box 146x 86x 40mm		Each	60
U-3	ELECTRIC WATER HEATER/ ROOM HEATER			
751	10 Ltrs		Each	9400
752	15 Ltrs		Each	NQ
753	25 Ltrs.		Each	10500
754	35 Ltrs		Each	11700
755	50 Ltrs		Each	15400
756	100 ltrs		Each	26200
757	500 ltrs		Each	NQ
758	1000 ltrs		Each	NQ
759	Room Heater (Double rod)		Each	1600
760	Room Heater (Single)		Each	1100
761	3 Strip hologen room heater		Each	4200
762	Holigen table lamp(standared size)		Each	NQ

763	Panel Heater,9 panels		Each	6200
764	Panel heater,11 panels		Each	7400
765	Bajaj Majesty Room Heater with remote control type		Each	NQ
766	(F118/ F117-Digital Convector-Atlantic Comfort Room Heater), 2000Watt, 98mm Depth, 754mm Width, 451mm Height and 5.2Kg in Weight.		Each	NQ
V-3	Metal boxes with suitable size of 4mm thick fibre sheet cover along with machine screws and cup washer			
767	75x75x60 mm(4"x4") 78*78mm		Each	NQ
768	100x100x60mm (4"x6") 78*100mm		Each	NQ
769	150x100x60mm (6"x8") 135*120mm		Each	NQ
770	180x150x60mm(8"x10") 205*215mm		Each	NQ
771	250x200x60mm 10"x12")		Each	NQ
772	300x200x60mm(12"x14")		Each	NQ
W-3	Sheet board (various size) with bakalite sheet			
773	4"x4"		Each	55
774	4"x6"		Each	65
775	6"x8'		Each	80
776	8"x10"		Each	110
777	10"x12"		Each	160
778	12"x14"		Each	185
779	Bakelite sheet (1.5mm thick)		Sq.m	NQ
X-3	Screws/Nails			
780	Machines screws 12mm		Pkt	180
781	Machines screws 20mm		Pkt	200
782	Machines screws 25mm		Pkt	240
783	Plastic dovels - 35mm		Pkt	260
784	Wooden Screws,12mm		Pkt	40
785	Wooden Screws,20mm		Pkt	45
786	Wooden Screw,25mm		Pkt	55
787	Cassing/Capping pin, 12mm		Pkt	50

788	Lighting Arrester, copper spikes		Each	9000
789	Copper trip 25X4mm		Meter	700
790	ALLUMINIUM LADDERS		Each	-
791	Single Wall Extension Ladder (2 section) (Model AL - 103) It can locks at any required height and adjustable Description : Side .c. section 65mm X 38mm Steps 25.4mm dia non slip corrugated tubing permanent punching in machine, fitted & operate with (Nylon) Polypropylene Rope pulley arrangement with bracket, lockable stoppers, solid rubber shoes and caps. (10 Ft to 45 Ft extended height)		Each	195000
	Self Support Extension Ladder (Model AL - 105) It can locks at any required height and adjustable Description : Side 'c section 65mm X 38mmSteps 25.4mm dia non slip corrugated tubing permanent punching in machine, fitted & operate with (Nylon) Polypropylene Rope pulley arrangement It with bracket, lockable stoppers, solid rubber shoes and caps (10 Ft to 45 Ft extended height)		Each	210000
792	Tester set	//Taparia	Each	170
793	Combination Plier	//Taparia	Each	240
794	Site cutting plair	//Taparia	Each	240
795	Long Nose Pliar	//Taparia	Each	240
796	Screw drivers set	//Taparia	Each	170
797	Soldering Iron		Each	200
798	Soldering Lead		Roll	130
799	155 Measuring tape 3m		Each	100

800	Drilling Machine (Light duty)		Each	2300
801	Drilling Machine (Heavy duty)		Each	4950
802	Drilling bit wooden all size		Each	NQ
803	Drilling bit metal all sizee		Each	NQ
804	Drilling bit concrete all size		Each	NQ
805	Wire guage (All the type wire to measure)		Each	NQ
86	Chisel		Each	NQ
807	Digital Multimeter		Each	2900
809	Fuse,6 or 5 amps		Each	60
810	Fuse,16 A		Each	60
811	Hand Saw Frame		Each	190
812	Hand saw blade		Each	8
813	Inlsulated hand Gloove		Each	290
814	Hammer (150-200g)		Each	NQ
815	Spiral Bit		Each	NQ
816	New Electri ceramic Tile marble saw 4" wet/dry cutter W.blade, Thin granite	//Marble cutter	Each	7500
817	Extersion Cord,16 Amps (Anchor)		Each	595
818	Extersion Cord,16 Amps (CONA)		Each	720
819	Conversion plug,2 pin		Each	16
820	PVC insulation Tape		Each	12
821	Transester Battery/9V		Each	NQ
822	Ballast (SON-T, 230V, A.C) HPF, 70Watt) (E)		Each	1100
823	Ballast (SON-T, 230V, A.C) HPF, 250 Watt)		Each	1700
824	Ballast (Mercury , 230V, A.C) HPF, 250 Watt)		Each	950
825	Ballast (Mercury , 230V, A.C) HPF, 125 Watt)		Each	900
LED FITTINGS				
1	Supplying of Maple type LED decorative Post top luminaires for 360 degree indirect light, resistant to impact and corrosion and glare free for better uniformity with IP 65 protection upto 40W			
	40watt	each		4785

2	Supplying of prewired pressure diecast aluminium housing high powered LED street light luminaire, having professional high quality optic lenses for wide angle beam, >100 lm/W, drive efficiency >90% , IP 65 protection class I, CRI >75, PF>0.95, surge protection 5KV, operating range 120-270V 50HZ, with lens & toughen glass including all accessories; driver, lamps			
	90W	each		NQ
	100 W	each		NQ
	60 W	each		NQ
3	Supplying of LED bulbs			
	5 watt	each		123
	7 watt	each		123
	9 watt	each		127
	12 watt	each		236
	14 watt	each		278
	23 watt	each		505
	27 watt	each		590
	45 watt	each		990
4	LED Tube complete			
	5 watt	each		304
	10 watt	each		370
	18 watt	each		405
	20 watt	each		405
	24 watt	each		478
5	LED Drivers for street light set			
	90W	each		NQ
	100 W	each		NQ
	60 W	each		NQ
6	Monoplast tape	mtr		NQ
7	Analog timer switch 24x7 16 /6 Amps	each		7000
8	Contact DP switch.			

	32A	each		4350
	40 A	each		4350
	63A	each		5220
9	Contactor TP switch.			
	32A	each		5075
	40 A	each		5075
	63A	each		5075
10	Jointing kits			
	16 sq mm	each		1230
	25 sqmm	each		1295
	35 sq mm	each		2465